

The **SEELVEL II**™ Tank Monitor



Model 711T

Features

- Provides accurate tank level information in percentage of full
- Fresh, grey and black water tanks are monitored using Garnet's proprietary external level sensing technology. This ends fouling problems caused by debris build-up in the holding tank
- Measures tanks up to 17 inches tall with a single sender or 33 inches tall with dual senders
- Detailed diagnostic information monitors sender operation
- Has built in temperature sensor
- Uses common industry connector for ease of installation and servicing

IT'S THE 21st CENTURY...WELCOME TO IT!

 **GARNET**
TECHNOLOGIES INC.

Your Dealer:

AA Solar & Sun Power Plus

34A Forge Road, Silverdale, Auckland 0932

Ph/Fax: 09 427 4040 Ph: 09 427 4143 Mob: 027 490 5901

www.aasolar.co.nz www.sunpowerplus.co.nz

sales@aasolar.co.nz sales@sunpowerplus.co.nz

MODEL 711T *SEELEVEL II*TM TANK MONITOR SPECIFICATIONS

Resolution:	1/4 inch (6 mm)
Accuracy:	+/- 5% or better, limited by resolution and tank shape
Operating temperature range:	+32 to +140 °F (0 to + 60°C)
Sender materials:	0.008" thick glass epoxy circuit board with conformal coating for circuit protection. Laminated on the back with 3M 300LSE Bonding Adhesive.
Display mounting panel:	Black panel, approximately 4 3/4" wide by 3 1/4" high by 1" thick (120mm wide X 83mm high X 25mm deep). Panel screws to wall. Required cutout size is 3 3/4" wide by 2 1/4" high.
System power requirements:	Display requires 12 volts from the RV battery, the system will function from 11 volts to 16 volts. Current drain is less than 200mA.
Wiring:	Two wire conductor required from the display to each sender and external temperature sensor. 12 V power and ground required for display.
Temperature sensor:	Semiconductor sensor with integral A/D converter. Accuracy +/- 3 degrees Fahrenheit (+/- 1.5 degrees Celsius).